La legrand®

Nuvo[®] P500 Player Portfolio Sound Bar and Subwoofer

Home audio has never sounded so good. The Player Portfolio Sound Bar (NV-P500-XX) provides excellent sound quality through a powerful 2.1 system, complete with an eight inch wireless subwoofer. The Sound Bar can play audio from a video source such as a TV or can be used within the Player Portfolio system to access a variety of streaming services as well as any networked audio content.



- Excellent sound quality through a powerful 2.1 system, complete with an eight inch wireless subwoofer
- Play audio from a video source, such as TV or DVD player
- Use as a Player zone giving you access to networked audio content and streaming services like Spotify, Pandora, iHeartRadio, and more
- Sleek design with metal grill and capacitive touch backlit control
- Easily controlled with the included IR remote, Nuvo PoE Keypads, or with the Nuvo Player app
- TOSLINK and analog line input
- Third-party integration with control partners such as Crestron, Control4, KNX, RTI, URC, and more
- Ethernet or Wireless 802.11 a,b,g,n, 2.4GHz or 5GHz

*Streaming services subject to geographic availability. Service subscriptions may be required.

Nuvo[®] P500 Player Portfolio Sound Bar and Subwoofer

Input/Output Connectors

Input/Output Connectors	
Line Input	RCA / TOSLINK
USB Connection	One
Local Area Network (LAN)	RJ45, Cat5 minimum,
	10/100baseT minimum
Supported Audio Formats	
Music File (USB or over netw	vork) MP3
-	WMA
	AAC
	Ogg Vorbis
	FLAC
	WAV
Internet Radio:	Pandora
	Sirius/XM
	iHeart Radio
	Tuneln
	Spotify
IP Control	Apple iTouch®
	Apple iPhone®
	Apple iPad®
	Android Mobile
	Android Tablet
Network Connectivity	
LAN (Wired Connection)	Ethernet,
Wire	less: 802.11 a,b,g,n 2.4 GHz or 5GHz band

Output

Distortion Frequency Response

Line Input:

Input Impedance Input Overload

Regulatory Approvals

Safety cTUVus, CE-LVD EMC US:FCC CFR Title 47 Part 15, Subpart B; CANADA:ICES-003; EUROPE:CISPR13; EUROPE: 55020; AUSTRALIA/NEW ZEALAND: C-TICK standard AS/NZS CISPR13 Environmental Compliance RoHS

0.5% max

10K Ohms

2.2 V RMS

50Hz - 20KHz

SPECIFICATIONS

Power Requirements

Input Voltage	110 – 240VAC, 50/60 Hz
Power Consumption (max)	120 W Soundbar; 80W Subwoofer
(typical - music)	75 W Soundbar; 50W Subwoofer
Operating Temperature	0° C to 40° C
Physical Specifications Soundbar Size without feet (mm) Soundbar Size without feet (inch) Subwoofer Size without feet (mm) Subwoofer Size without feet (inch)	
Soundbar Size with feet (mm)	115 H x 877 W x 115 D
Soundbar Size with feet (inch)	4.5 H x 34.5 W x 4.5 D
Subwoofer Size with feet (mm)	261 H x 231 W x 303 D
Subwoofer Size with feet (inch)	10.25 H x 9.1 W x 11.9 D
Soundbar Weight (kg)	4.65
Soundbar Weight (pounds)	10.25
Subwoofer Weight (kg)	4.69
Subwoofer Weight (pounds)	10.35
Shipping Specifications Unit Size (mm) Unit Size (inch) Unit Weight (kg) Unit Weight (pounds)	970 L x 315 W x 492.76 H 38.19 L x 12.4 W x 19.4 H 12.7 28
Languages Supported	English, Spanish, French

Portuguese, German, Italian

Legrand reserves the right to change specifications without notice.



Legrand, North America

3015 Kustom Drive Hebron, KY 41048 United States 844.334.8044 www.legrand.us/nuvo

designed to be better[™]